

## COLD BOX B 35 //logg

The B 35 //logg cold box is a small desktop appliance for cooling and freezing in all laboratories, research and industry. Due in particular to its compact space-saving design with a low-noise cooling unit, the cold box is suitable for direct use in the workplace. Equipped with a colour touch screen controller the cold box has various options of supervision, failure analysis, temperature logger and remote maintenance.



| Model                         | B 35-50 //logg | B 35-85 //logg |
|-------------------------------|----------------|----------------|
| Temperature range [min/max]   | -50°C / -10°C  | -85°C / -50°C  |
| Control accuracy              | +/- 1 K        | +/- 1 K        |
| Volume                        | 35 l           | 35 l           |
| Interior [WxDxH]              | 42,5x30x28 cm  | 42,5x30x28 cm  |
| External dimensions [WxDxH]   | 58x76,5x58 cm  | 58x76,5x58 cm  |
| Weight                        | 65 kg          | 81 kg          |
| Electrical connection         | 230 V / 50 Hz  | 230 V / 50 Hz  |
| Ambient temperature [min/max] | +12°C / +30°C  | +12°C / +30°C  |

### Accessories:

- B 35-RS stainless steel shelf
- 5 drawers, each for 6 standard cryoboxes (133x133x53 mm)
- Extra gaps for optimal, uniform and rapid cooling of the entire frozen product

### Options:

- Circulation air fan in the interior for better temperature distribution (not in B 35-85)
- Your desired option is not listed? Just ask us!

### Characteristics:

- Colour touch screen controller with representation of the temperature profile and user friendly menu structure
  - Integrated data logger readable over USB stick for temperature profile and alarm events
- Battery-supplied alarm more than at least 72h with indication of the max. temperature reached at the interior
- Ethernet interface | in case of an alarm E-Mail will be sent
- Automatic and detailed supervision function of the refrigerating machine with failure analysis
- Remote maintenance with a worldwide access over the Internet
- Detailed user administration to protect the adjusted alarm- and temperature set points
  - Registered access control
- Vacuum-Insulation: large interior space with small external dimensions and low power consumption
- All stainless steel casing
- Refrigeration unit: low noise, fully hermetically sealed, air-cooled, low maintenance
- B 35-85 //logg: two-stage cascade refrigeration system
- Foamed door with double door seal
- Interior free of fixtures: no ignition sources, makes cleaning easy
- Side air vent, so suitable for installation directly on walls
- Potential-free contact for connection to an external alarm system
- 100mV/K-output for connection to a temperature recording system
- Bushing (diameter 10 mm), e.g. for temperature monitoring with external sensors
- Lockable door
- Stackable unit, max. 2 units